

Pellacoat

Description: Pellacoat is a molasses based pellet de-duster. It is a blend of molasses (a by-product consisting of the syrupy residue collected during the manufacture or refining of sugar from sugar cane/beet) condensed molasses solubles (a high protein by product from the fermentation of molasses in the production of alcohol, yeast, citric acid & organic acids), soya oil, emulsifier, mould inhibitor and flavours.

Typical Analysis (As Fed Basis):

Dry Matter	62%
ME	7.0 MJ/kg
Crude Protein	11.0% (± 2%)
Sugar (as sucrose)	18.0% (± 2%)
Fibre	Nil
Oil	1.9%
Ash	12.0% (± 2%)
Calcium	0.6%
Magnesium	0.4%
Phosphorus	0.1%
Potassium	2.2%
Sodium	0.8%

Physical Properties:

Specific Gravity	1.3
Viscosity (cp at 20°C)	200
Viscosity Range	60-300
Ph.	5.0
Litres/tonne	752
Gallons/tonne	165

Appearance: Dark brown syrupy liquid.

Storage: Can be safely stored in vented waterproof tanks for up to 6 months.

Inclusion: Include at 0.5-0.8% in the finished feed after sieving.

Key Benefits:

- ✓ Cost-effective alternative to fats coating to reduce dust;
- ✓ Highly palatable;
- ✓ Absorbed rapidly into pellets;
- ✓ Enhances visual appearance of pellets;
- ✓ Excellent handling characteristics.

Delivery: Pellacoat is available in bulk deliveries nationwide, ranging from 10 up to 28 tonnes.



Contact: Premier Molasses Co. Ltd.
: Harbour Road, Foynes Co. Limerick.
: Deepwater Berth, Ringaskiddy Co. Cork
T: 069 65311 **F:** 069 65537
E: info@premiermolasses.ie

